

RF Solution offer a wide selection of 4 Ways Power Divider for global customers. PD04-F1186-N-698-3800MHz is a 4 Ways Power Divider in Frequency Range of 698~3800 MHz. It is made of high quality materials under a high standard, the Insertion Loss Max of this product is 1.2 dB, Isolation Min is 20 dB and Split Loss is 6.0 dB. The component has a good working performance and stability, it is ideal for handling a Rated Power of 50 W.

## **Product Details**

| Part Number | PD04-F1186-N-698-3800MHz          |
|-------------|-----------------------------------|
| Description | 698~3800 MHz 4 Ways Power Divider |

## **General Parameters**

| Frequency Range       | 698~3800 MHz   |
|-----------------------|----------------|
| Insertion Loss Max    | 1.2 dB         |
| Isolation Min         | 20 dB          |
| Split Loss            | 6.0 dB         |
| Rated Power           | 50 W           |
| VSWR Max              | 1.30           |
| Waterproof Grade      | IP65           |
| Relative Humidity Max | 95%            |
| Impedance             | 50 Ω           |
| Connector Type        | N-F            |
| Size                  | 108*86*21 mm   |
| Weight                | /              |
| Surface Finishing     | Black Painting |
| Operating Temperature | -20~+60 °C     |



## PD04-F1186-N-698-3800MHz

698~3800 MHz 4 Ways Power Divider

**ROHS** Compliant

Yes

## **Outline Drawing (mm)**

