



RF Solution offer a wide selection of Flanged Attenuator for global customers. RFT20N-60AM1663-6 is a Flanged Attenuator in Frequency Range of DC~6.0 GHz. It is made of high quality materials under a high standard, the Attenuation Value of this product is 20 dB, Attenuation Tolerance is  $\pm 0.8$  dB and VSWR Max is 1.25. The component has a good working performance and stability, it is ideal for handling a Rated Power of 60 W.

## Product Details

Part Number	RFT20N-60AM1663-6
Description	DC~6.0 GHz Flanged Attenuator

## General Parameters

Frequency Range	DC~6.0 GHz
Attenuation Value	20 dB
Attenuation Tolerance	$\pm 0.8$ dB
VSWR Max	1.25
Rated Power	60 W
Impedance	50 $\Omega$
Temperature Coefficient Max	150 ppm/ $^{\circ}\text{C}$
Size	Refer to the design drawing
Substrate Material	AlN
Porcelain Hat Material	Al <sub>2</sub> O <sub>3</sub>
Flange	Nickel-plated Copper
Lead	99.99% Sterling Silver
Resistance Technology	Thick Film
Operating Temperature	-55 to +150 $^{\circ}\text{C}$



ROHS Compliant

Yes

## Outline Drawing (mm)

